AMENDMENTS

In the Claims

Please enter the following amendments to the claims:

- 1. (Original) A method for inhibiting reading of an optical disc, comprising the following steps:
 - (a) providing an optical disc comprising machine-readable, information-encoding features, and a reading-inhibit agent, said inhibit agent activated by optical radiation and operative, once activated, to alter the disc to inhibit reading and to provide a short effective life for the disc;
 - (b) providing a reading device operative to read the disc, said reading device comprising a source of optical radiation; and
 - (c) reading the disc with the source while concurrently activating the inhibit agent with optical radiation from the source.
- 2. (Original) A method for inhibiting reading of an optical disc, said method comprising the following steps:
 - (a) providing an optical disc comprising:

machine-readable, information-encoding features;

- a barrier layer releasably coupled to the disc, said barrier layer configured to prevent machine reading of the features; and,
- a reading-inhibit agent, included in the disc and activated by removal of the barrier layer, said reading-inhibit agent operative, once activated, to initially allow reading of the disc, and then to alter the disc to inhibit reading of the disc; then
- (b) removing the barrier layer to allow machine reading of the features and to activate the reading inhibit agent; then,
- (c) reading the disc after removal of the barrier layer but before the disc is altered by

the reading inhibit agent to inhibit reading of the disc; and then,

- (d) said reading-inhibit agent then altering the disc to provide a short effective life for the disc.
- 3. (Original) The invention of claim 2 wherein the disc comprises a first surface, wherein the features are adjacent the first surface, wherein the inhibit agent is adjacent the features: and wherein the barrier layer is adjacent the inhibit agent.
- 4. (Original) The invention of claim 2 wherein the disc comprises a translucent layer operative to transmit a beam of light toward the features, wherein the inhibit agent is incorporated in or adjacent to the translucent layer, and wherein the barrier layer comprises a sheet adjacent the translucent layer.
- 5. (Original) The invention of claim 2 wherein the disc comprises a reflective film, and wherein the inhibit agent comprises a corrosion-enhancing agent disposed in or adjacent to the reflective film.
- 6. (Original) The invention of claim 2 wherein the inhibit agent is operative, once activated, to alter a physical dimension of the disc.

Claims 7-19 are canceled.

- 20. (New) The optically readable medium according to claim 60, wherein said reading-inhibit agent is located in the path of the incident optical read beam.
- 21. (New) The optically-readable medium according to claim 60, wherein said reading-inhibit agent is selected from one of an oxidizable material, a dye, a hygroscopic material, a photoreactive material, or a combination thereof.

Claims 22-24 are canceled.

25. (New) The optically-readable medium according to claim 60, wherein said reading-

inhibit agent inhibits reading of the at least a portion of said information encoded features by one of absorbing light from the optical beam, altering the reflectivity of the reflective layer, or physically distorting or altering a portion of the optically-readable medium.

Claims 26-32 are canceled.

33. (New) The optically-readable medium according to claim 60, wherein said reading-inhibit agent is activated by optical radiation.

Claims 34-37 are canceled.

- 38. (New) The optically-readable medium according to claim 60, wherein said short effective life for said optically-readable medium is determined by the number of times the at least a portion of the information encoded features is read by the optical beam.
- 39. (New) <u>The optically-readable medium according to claim 60, wherein said reading-inhibit agent corrodes the at least a portion of the information encoded features.</u>
- 40. (New) The optically-readable medium according to claim 60, wherein said reading-inhibit agent, once activated, increases optical scattering of the at least a portion of the information encoded features.
- 41. (New) The optically-readable medium according to claim 60, wherein said readinginhibit agent, once activated, inhibits reading by the optical beam by promoting deterioration of the at least a portion of the information encoded features.
- 42. (New) <u>The optically-readable medium according to claim 60, wherein said reading-inhibit agent, once activated, interferes with the optical beam.</u>

Claims 43-58 are canceled.

59. (New) An optically-readable medium comprising:

an information encoded region, said information encoded region readable by an optical beam from a reading device;

- at least one reading-inhibit agent in communication with at least one of a portion of said
 information encoded region and the optical beam, wherein said at least one
 reading-inhibit agent inhibits reading of at least a portion of said information
 encoded region by the optical beam after a predetermined period of time after
 removal of an enclosure; and
- the enclosure enclosing said optically-readable medium wherein said at least one readinginhibit agent provides a short effective life for said optically-readable medium.
- 60. (New) An optically-readable medium, comprising:
 - at least one substrate having information encoded features with a reflective layer to
 reflect an incident optical read beam so that the optical read beam may read
 the information encoded features; and
 - a reading-inhibit agent included in the optically-readable medium that, once operative,

 prevents at least a portion of the information encoded features from being read by
 the incident optical read beam wherein said reading-inhibit agent provides a short
 effective life for said optically-readable medium.

Claim 61 is canceled.

- 62. (New) The optically-readable medium according to claim 59, wherein said reading-inhibit agent is selected from one of an oxidizable material, a dye, a hygroscopic material, a photoreactive material, or a combination thereof.
- 63. (New) The optically-readable medium according to claim 59, wherein said readinginhibit agent inhibits reading of the at least a portion of said information encoded features by one of absorbing light from the optical beam, altering the reflectivity of the reflective layer, or physically altering a portion of the optically-readable medium.